



PG L

2235·2335·2435



EFFICIENCY. IT'S BLACK AND WHITE

EFFICIENCY MEANS MAXIMISING SPACE AND TIME

The Olivetti **PG L2235**, **PG L2335** and **PG L2435** printers are ideal for users looking for outstanding performance in an affordable, space-saving device. Efficient, reliable and compact, suitable for individual users and small work groups, they guarantee **fast, professional results** with a top speed of 35 pages per minute and the first printed page produced in under 8 seconds.

EFFICIENCY MEANS TAKING CARE OF THE ENVIRONMENT

To reduce their impact on the environment, the Olivetti PG L2235, PG L2335 and PG L2435 printers guarantee **low Typical Electricity Consumption (TEC)** values, low emissions, low noise levels, long-life consumables and, through duplex printing, reduced paper consumption.

EFFICIENCY MEANS USING THE BEST TECHNOLOGY

The network card is an option for the PG L2235 and PG L2335 printers, while the PG L2435 comes with an integrated network card and can be fitted with an optional second network card and Wireless LAN. The LCD display on the PG L2435 allows the user to print directly from a USB memory stick at the device.

EFFICIENCY MEANS GOOD RESULTS FOR EVERYONE

Expandable memory, optional network cards, expandable paper storage capacity and reduced costs make the PG L2235, PG L2335 and PG L2435 printers suitable for a wide variety of requirements, with a guarantee of high print quality.



MAXIMUM PRINT SPEED: 35 PPM IN A4

COMPACT AND ROBUST

VERY LOW TEC VALUES

LONG-LIFE CONSUMABLES

STANDARD NETWORK INTERFACE: PG L2435

OPTIONAL NETWORK INTERFACE:

PG L2235 / PG L2335

DIRECT PRINTING FROM USB MEMORY STICK / LCD DISPLAY FOR THE PG L2435

MONO DIGITAL PRINTERS



Compact and manageable



LED Button (PG L2235/PG L2335)
LCD Operator Panel (PG L 2435)



USB Port for Direct printing
from Memory Stick (PG L 2435)



Flexible paper management

TECHNICAL SPECIFICATIONS

PRINTER	PG L 2235	PG L2335	PG L 2435
Technology	Laser, black and white, A4		
Printing Speed	Up to 35 ppm		
First Page Out	6 seconds	6 seconds	8 seconds
Warm-up Time	15 seconds	15 seconds	16.5 seconds
CPU	PPC 405F5 360 MHz	PPC 405F5 360 MHz	PPC 465 500 MHz
Standard/Max. Memory	32 MB / 544 MB	32 MB / 544 MB	256 MB / 1280 MB
Resolution	1200 x 1200 dpi		
Operator Panel	LED	LED	LCD
Interfaces	USB 2.0 CF-Card port	USB 2.0 CF-Card port	USB 2.0, USB Host 2.0 SD/SDHC Card port (max. 32GB) Network card 10Base-T/100Base-TX/1000Base-T AirPrint® Mobile Printing Support
Emulations	PCL6 (5e, XL), KPDL3 (PS3 Windows compatible) with Automatic Emulation Switching, Line Printer, IBM Proprinter X24E, EPSON LQ-850, DIABLO 630 (PG L2235 / PG L2335), PDF 1.7 (PG L2435), XPS (PG L2435)		
Operating Systems	All current Windows operating systems, Mac OS X version 10.5 or higher, Unix, Linux		
Fonts	80 scalable fonts (PCL6/ KPDL3) accessible on all emulations, 1 bitmap font, 45 mono-dimensional barcodes, 1 two-dimensional barcode (PDF-417)		

PAPER MANAGEMENT

Multi-purpose Input Tray (MPT)	50 sheets (80g/m ² standard) up to A4/ Letter size 148 x 210 – 215.9 x 297 (mm) + LGL, FOL, OF2		
Standard Paper Tray	250 sheets (80g/m ²) 105 x 148 – 215.9 x 297 (mm) + LGL, FOL, OF2		
Optional Paper Tray	1 x 250 sheets	2 x 250 sheets	2 x 250 sheets
Maximum Paper Capacity with Options	550 sheets	800 sheets	800 sheets
Duplex Unit	Standard: A5R, A4, Letter, Legal, Folio, Oficio 2, 60 - 105 g/m ²		
Output Tray Capacity	250 sheets		

GENERAL CHARACTERISTICS

TEC (kWh/week)	1.73	1.73	1.906
Noise level	Print mode: (max. speed) 53.3 dB(A) LpA Stand-by: 30.7 dB(A) LpA	Print mode: (max. speed) 53.5 dB(A) LpA Stand-by: 30.4 dB(A) LpA	Print mode: (max. speed) 53.5 dB(A) LpA Stand-by: N/A
Energy consumption	Print mode: 535 W Stand-by: 7.1 W Sleep: 2.6 W Off: 0.5 W or less	Print mode: 535 W Stand-by: 7.1 W Sleep: 2.6 W Off: 0.5 W or less	Print mode: 499 W Stand-by: 11 W Sleep: 2.5 W Off: 0.1 W or less
Power	220/240 V, 50/60 Hz		
Dimensions (W x D x H)	375mm x 393mm x 250mm	375mm x 393mm x 250mm	516mm x 506mm x 395mm
Weight	12Kg	12Kg	14Kg

CONSUMABLES

Black Toner Capacity (ISO/IEC 19752)	Up to 2,500 A4 pages	Up to 7,200 A4 pages	Up to 7,200 A4 pages
Starter Toner (ISO/IEC 19752)	Up to 1,000 A4 pages	Up to 2,300 A4 pages	Up to 2,300 A4 pages
Maintenance Kit	Up to 100,000 pages		

OPTIONS

Paper Tray (PF-100)	250 sheets (80g/m ²) 105 x 148 – 215.9 x 297 (mm) + LGL, FOL, OF2		
Memory Expansion	128/512 MB DIMM	128/512 MB DIMM	512 MB/1 GB DIMM
Network Interface (IB-23)	Optional	Optional	N/A
Second Network Card (IB-50)			Gigabit Ethernet 10BaseT/100BaseTX/1000BaseT
Wireless Network Interface (IB-51)			Wireless Lan 802.11 b/g/n

Product performances are referred to as appropriate use under optimal conditions. The registered trademarks are the property of their respective owners.

The support and availability of the listed specifications and functionalities varies depending upon operating systems, applications, network protocols as well as network and system configurations. All information relating to specification and accessories is subject to change without notice. Olivetti does not guarantee that any prices or specifications mentioned will be error-free.
The PG L2235, PG L2335 and PG L2435 are distributed by Olivetti S.p.A. (07/14) Code: 29305-00

OLIVETTI UK LIMITED.
500 AVEBURY BOULEVARD
MILTON KEYNES, MK9 2BE
www.olivettiuk.com

